

TECHNICAL SPECIFICATIONS SUBMITTAL FORM

Job Name:	Submittal Date:	Wholesaler:
Job Location:	Engineer/Architect:	Contractor:

Product Use:

Filter Driers for use in HVAC and Refrigeration applications.

Design and Features:

- Body design manufactured with advanced welding technology for leak-free joints and superior performance with high-pressure refrigerants.
- Finished with semi-gloss black epoxy-polyester powder coat paint tested to 1,000 hours of salt spray, exceeding ASTM standards.
- Desiccant comprised of molecular sieve and activated alumina in a ratio of 80:20.
- Strong and rust-free furnace-brazed threaded fittings.
- Recommended for Commercial Air Conditioning, Commercial Refrigeration, Cold Chains, Precision Air Conditioners, Industrial Refrigeration, Food Retail.
- Furnace brazed pure copper ends, boasting both longer length and thicker walls when juxtaposed with other brands' offerings.
- Uses honey-comb design perforated plate to minimize pressure drops.
- Solid core type with XH-11 grade molecular sieves.
- One-year warranty.

Certifications and Approvals:

- CE
- UL-Listed

Selection:

- Solid Core Bi-Flow Filter Driers
- Solid Core Bi-Flow Filter Driers with TW
- Press Compatible Solid Core Bi-Flow Filter Driers
- Press Compatible Solid Core Bi-Flow Filter Driers with TW








NCHBF-S Dimensions

DART #		OUTER DIA. ØA		ENGTH B	STOPPER TO STOPPER LENGTH		OVERALL LENGTH D		CONNECTION	WT (LB)	WT (C)	
PART #	ММ	IN	ММ	IN	ММ	IN	ММ	IN	TYPE (IN)	WI (LD)	WT (G)	
NCHBF-052S			76	2.00//	106	4.17"	126	4.06"	1/4" ODF	1.435	651	
NCHBF-053S		5 Ø 2.5"	76	2.99"	102.3	4.03"	126	4.96"	3/8" ODF	0.972	441	
NCHBF-082S	Ø 63.5				127	5"			1/4" ODF	1.213	550	
NCHBF-083S				97	3.82"	123.3		147	5.79"	3/8" ODF	1.202	545
NCHBF-084S					123.3	4.85"			1/2" ODF	1.257	570	
NCHBF-163S				4.61"		5.64"	167	6.57"	3/8" ODF	1.918	870	
NCHBF-164S			117		143.3				1/2" ODF	2.088	947	
NCHBF-165S									5/8" ODF	1.982	899	
NCHBF-303S	Ø 76.2	Ø 3"							3/8" ODF	3.505	1590	
NCHBF-304S			101	7.52"	247.2	0.56"			1/2" ODF	3.505	1590	
NCHBF-305S			191		217.3	8.56"	241	9.49"	5/8" ODF	3.505	1590	
NCHBF-306S									3/4" ODF	3.505	1590	

NCHBF-S Dimensions

NCHBF-05	52S	1/4" Bi-Flow Filter Drier
NCHBF-05	53S	3/8" Bi-Flow Filter Drier
NCHBF-08	82S	1/4" Bi-Flow Filter Drier
NCHBF-08	83S	3/8" Bi-Flow Filter Drier
NCHBF-08	845	1/2" Bi-Flow Filter Drier
NCHBF-16	63S	3/8" Bi-Flow Filter Drier
NCHBF-16	54S	1/2" Bi-Flow Filter Drier
NCHBF-16	65S	5/8" Bi-Flow Filter Drier
NCHBF-30	03S	3/8" Bi-Flow Filter Drier
NCHBF-30	045	1/2" Bi-Flow Filter Drier
NCHBF-30	05S	5/8" Bi-Flow Filter Drier
NCHBF-30	D6S	3/4" Bi-Flow Filter Drier



The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of a product.

All installations must completely comply with all NDL Industries warnings and instructions, national state and local codes and all applicable ANSI standards.

NDL Industries product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Customer












NCHBF-F Dimensions

DART #	OUTE Ø			BODY LENGTH B		. LENGTH D	CONNECTION TYPE	VA/T (I D)	WT (G)	
PART #	ММ	IN	ММ	IN	ММ	IN	(IN)	WT (LB)	WI (G)	
NCHBF-052F			7.0	2.00%	122	4.8"	1/4" SAE	1.435	651	
NCHBF-053F			76	2.99"	130	5.12"	3/8" SAE	1.435	651	
NCHBF-082F	Ø 63.5	Ø 2.5"			143	5.63"	1/4" SAE	1.257	570	
NCHBF-083F			97	3.82"	151	5.94"	3/8" SAE	1.279	580	
NCHBF-084F					157	6.18"	1/2" SAE	1.841	835	
NCHBF-163F				4.61"	171	6.73"	3/8" SAE	1.962	890	
NCHBF-164F			117		177	6.97"	1/2" SAE	2.315	1050	
NCHBF-165F					185	7.28"	5/8" SAE	2.088	947	
NCHBF-303F	Ø 76.2	Ø 3"			246	9.65"	3/8" SAE	3.505	1590	
NCHBF-304F			101	7.52"	251	9.88"	1/2" SAE	3.505	1590	
NCHBF-305F			191	7.52"	259	10.2"	5/8" SAE	3.505	1590	
NCHBF-306F				-	265	10.43"	3/4" SAE	3.505	1590	

NCHBF-F Dimensions

NCHBF-052F	1/4" Bi-Flow Filter Drier
NCHBF-053F	3/8" Bi-Flow Filter Drier
NCHBF-082F	1/4" Bi-Flow Filter Drier
NCHBF-083F	3/8" Bi-Flow Filter Drier
NCHBF-084F	1/2" Bi-Flow Filter Drier
NCHBF-163F	3/8" Bi-Flow Filter Drier
NCHBF-164F	1/2" Bi-Flow Filter Drier
NCHBF-165F	5/8" Bi-Flow Filter Drier
NCHBF-303F	3/8" Bi-Flow Filter Drier
NCHBF-304F	1/2" Bi-Flow Filter Drier
NCHBF-305F	5/8" Bi-Flow Filter Drier
NCHBF-306F	3/4" Bi-Flow Filter Drier



The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of a product.

All installations must completely comply with all NDL Industries warnings and instructions, national state and local codes and all applicable ANSI standards.

NDL Industries product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Customer












NCHBF-S Dimensions

PART #		OUTER DIA. BODY LENGTH ØA B		STOPPER TO ST	OVERALL LENGTH D		CONNECTION	MT (LB)	WT (C)			
	ММ	IN	ММ	IN	ММ	IN	ММ	IN	TYPE (IN)	WT (LB)	WT (G)	
NCHBF-307S	- Ø 76.2	Ø 76.2	Ø 3"	101	7.52"	221	8.7"	265	10.43"	7/8" ODF	2 505	1500
NCHBF-309S			ט 3	191	7.52	221	0.7	275	10.83"	11/8 ODF	3.505	1590



NCHBF-S Dimensions

NCHBF-307S	7/8" Bi-Flow Filter Drier
NCHBF-309S	1-1/8" Bi-Flow Filter Drier

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of a product.

All installations must completely comply with all NDL Industries warnings and instructions, national state and local codes and all applicable ANSI standards.

NDL Industries product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Customer












Press Compatible Solid Core Bi-Flow Filter Driers

NCHBF-Z Dimensions

PART #	OUTER DIA. ØA		BODY LENGTH B		STOPPER TO STOPPER LENGTH C		OVERALL LENGTH D		CONNECTION	WT (LB)	WT (G)
	ММ	IN	ММ	N	ММ	IN	ММ	IN	TYPE (IN)	WT (LB)	WT (G)
NCHBF-083-Z	Ø 63.5 Ø	Ø 2.50"	97	3.81"	51.5	2.02"	200	7.87"	2/9" ODM	1.235	560.2
NCHBF-163-Z		ע 2.50	117	4.60"			220	8.66"	3/8" ODM	1.984	899.9



NCHBF-Z Dimensions

NCHBF-083-Z	3/8" Bi-Flow Filter Drier (Press Compatible)
NCHBF-163-Z	3/8" Bi-Flow Filter Drier (Press Compatible)

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of a product.

All installations must completely comply with all NDL Industries warnings and instructions, national state and local codes and all applicable ANSI standards.

NDL Industries product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Customer












Solid Core Bi-Flow Filter Driers with TW

NCHBF-S-TW Dimensions

PART #		OUTER DIA. ØA		ENGTH B	STOPPER TO ST	OPPER LENGTH		. LENGTH	CONNECTION	WT (LB)	WT (G)				
	ММ	IN	ММ	IN	ММ	IN	ММ	IN	TYPE (IN)	WI (LB)	WI(G)				
NCHBF-052S-TW			76	2.99"	106	4.17"	126	4.96"	1/4" ODF	1.436	651.4				
NCHBF-083S-TW	Ø 63.5	Ø 2.5"	0.7	2.02//	122.2	4.05#	147	5.79"	3/8" ODF	1.202	545.0				
NCHBF-084S-TW			97	3.82"	123.3	4.85"	147	3.75	1/2" ODF	1.842	835.6				
NCHBF-163S-TW													3/8" ODF	1.918	870.0
NCHBF-164S-TW			117	4.61"	143.3	5.64"	167	6.57"	1/2" ODF	2.083	945.0				
NCHBF-165S-TW	0.76.2								5/8" ODF	2.151	975.8				
NCHBF-303S-TW	Ø 76.2	Ø 3"							3/8" ODF	3.525	1599.0				
NCHBF-304S-TW				191	7.52"	217.3	8.56"	241	9.49"	1/2" ODF	3.563	1616.0			
NCHBF-305S-TW									5/8" ODF	3.507	1590.8				

NCHBF-S-TW Dimensions

NCHBF-052S-TW	1/4" Bi-Flow Filter Drier with Tracer Wafer					
NCHBF-083S-TW	3/8" Bi-Flow Filter Drier with Tracer Wafer					
NCHBF-084S-TW	1/2" Bi-Flow Filter Drier with Tracer Wafer					
NCHBF-163S-TW	3/8" Bi-Flow Filter Drier with Tracer Wafer					
NCHBF-164S-TW	1/2" Bi-Flow Filter Drier with Tracer Wafer					
NCHBF-165S-TW	5/8" Bi-Flow Filter Drier with Tracer Wafer					
NCHBF-303S-TW	3/8" Bi-Flow Filter Drier with Tracer Wafer					
NCHBF-304S-TW	1/2" Bi-Flow Filter Drier with Tracer Wafer					
NCHBF-305S-TW	5/8" Bi-Flow Filter Drier with Tracer Wafer					



The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of a product.

All installations must completely comply with all NDL Industries warnings and instructions, national state and local codes and all applicable ANSI standards.

NDL Industries product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Customer












Solid Core Bi-Flow Filter Driers with TW

NCHBF-S-TW Dimensions

PART #		OUTER DIA. BODY LEN ØA B			STOPPER TO ST	OVERALL LENGTH D		CONNECTION)A/T (I D)	WT (C)	
	ММ	IN	ММ	IN	ММ	IN	ММ	IN	TYPE (IN)	WT (LB)	WT (G)
NCHBF-307S-TW	Ø 76.2	Ø 3″	191	7.52"	221	8.7"	265	10.43"	7/8" ODF	3.713	1684.0



NCHBF-S-TW Dimensions

NCHBF-307S-TW	7/8" Bi-Flow Filter Drier with Tracer Wafer
---------------	---

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of a product.

All installations must completely comply with all NDL Industries warnings and instructions, national state and local codes and all applicable ANSI standards.

NDL Industries product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Customer












Press Compatible Solid Core Bi-Flow Filter Driers with TW

NCHBF-Z-TW Dimensions

DART #	OUTER DIA. ØA		BODY LENGTH B		STOPPER TO STOPPER LENGTH C		OVERALL LENGTH D		CONNECTION	WT (LB)	NAT (C)
PART #	ММ	IN	ММ	IN	ММ	IN	ММ	IN	TYPE (IN)	WT (LB)	WT (G)
NCHBF-083-Z	Ø 63.5	Ø 2 E0"	97	3.81"	51.5	2.02	200	7.87"	- 3/8" ODM	1.246	565.2
NCHBF-163-Z		ע 63.5 ע	3.5 Ø 2.50"	117	4.60"	51.5	2.02	220	8.66"	3/8 ODW	2.167



NCHBF-Z-TW Dimensions

NCHBF-083-Z-TW	3/8" Bi-Flow Filter Drier with Tracer Wafter (Press Compatible)
NCHBF-163-Z-TW	3/8" Bi-Flow Filter Drier with Tracer Wafter (Press Compatible)

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of a product.

All installations must completely comply with all NDL Industries warnings and instructions, national state and local codes and all applicable ANSI standards.

NDL Industries product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Customer







