

APPLICATIONS

Commercial, Industrial, and Residential CO₂ Refrigeration

C194 Copper Ball Valves (CO2-C)

NDL CO₂ ball valves perform unlike any other in its class for leak prevention, reliability, and superior field performance.



CO2-C Specifications

Exceptional Safety Margins

Our valves can hold five times their maximum working pressure, netting a tremendous safety margin for any ball valve used in ${\rm CO}_2$ systems.

Quality Tested

Each valve is helium tested at the factory to guarantee leakfree performance.

Bottom-Up Stem Installation

Our stem placement is engineered from the bottom up. If there is an accidental over-pressurization in the valve, it will not blow the stem out and lose the charge.

Stainless Steel Body

The NDL CO2 valves feature a stainless steel body for stainless steel and copper-alloy connections.

Size and Connections

A wide range of sizes and connection types makes our valves compatible with main pipe types manufactured from copper iron alloys and stainless steel.

Unparalleled Two-year Warranty

Our warranty proves confidence, along with stamping every valve with a serial number and cleanly packaging in a polybag to prevent contamination and malfunctions.




Operating Specifications


- Temperature: -40° to 302°F (-40°C to 150°C)
- Burst Pressure: 5 times the working pressure
- Life Expectancy: >50,000 cycles

Certifications and Approvals

- RoHS
- UL-listed
- CE-approved
- · CRN-approved







CO2-C Sizes, Kv/Cv, and Pressure Ratings

PART NUMBER	CONNECTION ODS	BALL PORT SIZE	KV	cv	MAXIMUM OPERATING PRESSURE	
	IN	ММ	M3/H	GPM	BAR	PSI
CO2-02C	0.25"	10	0.8	0.9	140	2030
CO2-03C	0.375″	10	3	3.5	140	2030
CO2-04C	0.5"	10	5	5.8	140	2030
CO2-05C	0.625"	14	17	19.7	140	2030
CO2-06C	0.75"	18	17	19.7	140	2030
CO2-07C	0.875"	19	29	33.5	140	2030
CO2-09C	1.125"	25	51	59.0	140	2030
CO2-11C	1.375"	31	81	93.6	140	2030
CO2-13C	1.625"	37	105	121.4	120	1740
CO2-17C	2.125"	50	214	247.4	120	1740





