

NDL P/AC Copper Fittings

Product Information

Exceptional Copper Quality

- NDL copper fittings meet ASME B16.22 wall thickness standards, ensuring exceptional durability and long-lasting performance.

Precise Tolerances for Better Connections

- Tight tolerances create stronger joints and enable faster, more reliable brazing.

Certifications and Approvals

- NDL fittings are CRN-approved and easily identifiable
- Each fitting is clearly size-stamped for quick identification in the field and during sales. Complies with ANSI/ASME B16.22, B16.29, B16.18, B16.15, B16.26, B16.24, and B16.23 standards

1-Year Warranty

- NDL offers a 1-year warranty on the entire PAC Copper Fitting product line, providing peace of mind and long-term reliability.



Technical Data

SIZE (IN)	PSI (200°F)	BAR (93°C)	PSI (250°F)	BAR (121°C)
1/4"	740	51.3	725	50.2
3/8"	740	51.3	725	50.2
1/2"	635	43.8	620	42.9
5/8"	585	40.6	575	39.8
3/4"	515	35.5	505	34.8
7/8"	475	32.7	465	32.1
1-1/8"	400	27.8	395	27.2
1-3/8"	355	24.7	350	24.2
1-5/8"	330	23	325	22.5
2-1/8"	295	20.4	290	20
2-5/8"	270	18.9	265	18.5
3-1/8"	255	17.8	250	17.4
3-5/8"	245	17	240	16.7
4-1/8"	235	16.5	230	16.1
5-1/8"	215	15.1	215	14.8
6-1/8"	200	14.1	200	13.8

Pressure Ratings Based on ASME B16.22



Explore our full line of high-quality HVAC-R, CO₂ Refrigeration, and Hydronic products.

ndlindustries.com | 1-866-635-6888 | sales@ndlinc.com

@ndlindustries





Product Sizes and Selection



Female Adapters

Min. Size: 5/8" x 1/2"
Max. Size: 2-1/8" x 2"



Roll Stop Couplings

Only Size: 1-5/8"



90° Short Radius Elbows

Min. Size: 1/4"
Max. Size: 4-1/8"



Female Street Adapters

Min. Size: 5/8" x 1/2"
Max. Size: 2-1/8" x 2"



Stake Stop Couplings

Min. Size: 3/8"
Max. Size: 2-1/8"



90° Short Radius Street Elbows

Min. Size: 1/4"
Max. Size: 4-1/8"



Male Adapters

Min. Size: 5/8" x 3/8"
Max. Size: 2-1/8" x 2"



45° Elbows

Min. Size: 1/4"
Max. Size: 2"



P-Traps

Min. Size: 5/8"
Max. Size: 1-1/8"



Male Street Adapters

Min. Size: 7/8" x 3/4"
Max. Size: 2-1/8" x 2"



45° Street Elbows

Min. Size: 3/8"
Max. Size: 2-3/8"



Tees

Min. Size: 1/4"
Max. Size: 2-1/8"



Reducing Bushings

Min. Size: 3/8" x 1/4"
Max. Size: 2-1/8" x 1-3/8"



90° Long Radius Elbows

Min. Size: 1/4"
Max. Size: 3-1/8"



Reducing Tees

Min. Size: 3/8" x 3/8" x 1/2"
Max. Size: 1-5/8" x 1-5/8" x 1-3/8"



Caps

Min. Size: 3/8"
Max. Size: 2-1/8"



90° Long Radius Street Elbows

Min. Size: 3/8"
Max. Size: 3-1/8"



Unions

Min. Size: 1/2"
Max. Size: 2-1/8"



Reducing Couplings

Min. Size: 3/8" x 1/4"
Max. Size: 1-1/4" x 1/2"



Explore our full line of high-quality HVAC-R, CO₂ Refrigeration, and Hydronic products.

ndlindustries.com | 1-866-635-6888 | sales@ndlinc.com

@ndlindustries

